* PWM function,intelligent IR illumination & power consumption is variable,dependant the zoom factor
* IR distance up to 50 meters; English OSD
* Support ambient light detection,IR Illumination On 1-15 grade selectable
* Park Action incudes Home position. 360° scan/A-B scan/guard tour1-3
* 360°continuous rotation,horizontal :50°/s ,Vertical :30°/s ;
* Dome ID, baud rate, communication protocol can be changed from OSD
* Supported Protocols : Pelco-D/P; Others on special request.
* Power supply 12V DC , consumption is less than 20W;

BT-50F 4'' Mini IR Medium speed dome

Specifications:

Horizontal Rotation Speed	0.1°-50°/s
Horizontal Rotation Range	360°
Tilt Rotation Range	94°
Auto Flip	Horizontal 180°,Vertical 90°
Auto control IR LED	PWM
A-B Scan	User programmable
A-B Scan Speed	1～64 grade selectable
Dwell Preset	05-60s
Preset Points	128
Go to Preset Speed	50°/s
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable 02～60S
Park Action	Home position. 360° scan/A-B scan/guard tour 1-3
Part Time	1-60mins available
PWR on Action	Memory as power off/360° scan/A-B scan/guard tour1-3
Ambient light detection	Support
IR Illumination On	1-15 grade selectable
Communication Protocol	Pelco-D,Pelco-P
Communication	RS485
Baud Rate	1200/2400/4800/9600bps
Operating Temperature	Indoor:0°~ +40°
Operating humidity	≤95% Non Condensing
Power	DC12 ≤3A
IR Illumination Distance	up to 50 meters
Power Consumption	≤ 20W
Lightning protection	transient voltage 3000V
Compatible camara	SONY,LG,CNB,SAMSUMG (12*zoom) or board camera with fix lens.
LED Angle of Illumination	Ø16=2