

D-89 Series

Pan Tilt Zoom Colour Camera



D89 Series

The D89 Series PTZ has a compact structure, high stability, good anti-shock protection, has pan/tilt abilities and has improved image quality and improved working efficiency.

D89 Series PTZ has build-in zoom camera and decoder, it can pan 360° continuously, it can tilt 180°, with auto flip, this PTZ has no blind spot. High-test motor works equally at low speed and is able to accurately locate targets. The D89 Series PTZ can set up to 128 presets (titles can be set), 4 tours (Max 32 presets for each tour), 4 patterns (each record time is no less than 180s) and has 8 programmable zones with titles.



Specification

Power supply	DC 12V	Rotation	Pan 360° continuously tilt 180° □ □ 90° □ □ 90° □ □ with auto-flip	S/N ratio	≥50 db
Power consumption	40 W	Preset	128 preset, titles can be edited	Night-vision distance	100m
Scanning system	2:1 Interlacing	Auto-flip	Tilt down 90°, with auto-flip 180°	Focus	3.5-91mm
Imaging element	1/4" Sony Exview CCD	Display zone	8 programmable zones with titles	Angle of view	Wide 54° / tele 2.2°
Significant pixel (H*V)	752 (H) X 582 (V)	Alarm function	7 alarm input / 2 alarm output	Rotation speed	Pan 0.4 □ 80°/s □ Tilt 0.4 □ 60°/s
Baud rate (RS485)	2400 □ 4800 □ 9600/19200 bps	Sync Model	Internal/external	Preset Time	< 1 second
Monitor method	Manual/Time start-up setting	Resolution	≥480 TVLines	Decoder	Built-in
Net weight	12.0kg	Video output	1.0 +/-0.2Vp-p	Video output	Female BNC
Dimension (L*W*H)	411*270*384mm	Protection grade	IP66, TVS1500W lightning-proof, surge-proof, all-day defend cover		