

Secure life with **KCE**
Box camera



KCE-140D

Box Camera



- 1/3" Sony Dual Scan CCD
- 0.05Lux at F1.2 / 0.0002Lux (Sens-up)
- High Resolution 600TVL
- HSBL / 3D-DNR
- True WDR
- Auto Iris Lens Not Included

Specification

DESCRIPTION	NTSC	PAL
Image Sensor	1/3" Sony Dual Scan CCD	
Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
Scanning System	2:1 Interface	
Synchronization	Internal	
Horizontal Resolution	600TV Lines	
Video Output	CVBS : 1.0Vp-p, 75Ω composite	
S/N (Y Signal)	45dB (AGC off)	
Min. Illumination	0.05Lux at F1.2 / 0.0002Lux (Sens-up)	
OSD	Built-in	
IRIS Adjustment	MANUAL / DC	
Lens	C,CS Mount Lens	
Electronic Shutter	AUTO / MANUAL (1/60~1/100,000sec)	AUTO / MANUAL (1/50~1/100,000sec)
Backlight Compensation	BLC / WDR / HSBL / OFF	
White Balance	ATW / AWC / MANUAL(1,700K ~ 11,000K)	
AGC	OFF / LOW / MIDDLE / HIGH	
Day&Night	AUTO / EXT / DAY / NIGHT	
Privacy	ON / OFF (8 zones)	
3D-DNR	OFF / LOW / MIDDLE / HIGH	
Language	English / Japanese / German / French / Russian / Portuguese / Spanish	
Motion	ON / OFF (4 zones)	
Digital Zoom	ON / OFF (x1 ~ x8)	
DIS	ON / OFF	
WDR	LG DSP	
Input Voltage	DC 12V(±10%) / AC 24V Dual Voltage	
Power Consumption	DC 12V : 250mA(MAX) / AC 24V : 150mA(MAX)	
Operating Temp. / Hum.	-10°C ~ +50°C / 30% ~ 80% RH	
Storage Temp. / Hum.	-20°C ~ +60°C / 20% ~ 90% RH	

Dimension

Unit : mm

