

KCE-150-E

Box Camera



- 1/3" 960H Sony EXview HAD II CCD
- 0.1Lux at F1.2
- Super High Resolution 700TV Lines
- Built-in OSD Controller
- DNR(Digital Noise Reduction)
- Auto Iris vari-focal lens not included



Specification

| DESCRIPTION | NTSC | PAL |
|------------------------|---|-------------------------------------|
| Image Sensor | 1/3" 960H Sony EXview HAD II CCD | |
| Effective Pixels | 976(H) x 494(V) | 976(H) x 582(V) |
| Scanning System | 2:1 Interface | |
| Synchronization | Internal | |
| Horizontal Resolution | 700TV Lines | |
| Video Output | CVBS : 1.0Vp-p, 75Ω composite | |
| S/N (Y Signal) | 52dB (AGC off) | |
| Min. Illumination | 0.1 Lux at F1.2 | |
| OSD | Built-in | |
| IRIS Adjustment | MANUAL / AUTO(DC) | |
| Lens | C,CS Mount Lens | |
| Electronic Shutter | AUTO / MANUAL (1/60~1/10,000sec) | AUTO / MANUAL (1/50~1/10,000sec) |
| Backlight Compensation | BLC / HLC / OFF | |
| White Balance | ATW / PUSH / USER1 / USER2 / ANTI CR / MANUAL / PUSH LOCK | |
| AGC | MANUAL / AUTO | |
| ATR | ON / OFF | |
| Mirror | ON / OFF | |
| Day&Night | COLOR / AUTO / B/W | |
| Privacy | ON / OFF (4 zones) | |
| DNR | Y/C Level Adjustment | |
| Language | English / Japanese / German / French / Russian / Portuguese / Spanish | |
| Motion | ON / OFF | |
| Input Voltage | DC 12V(±10%) / AC 24V Dual Voltage | |
| Power Consumption | DC 12V : 250mA(MAX) / AC 24V : 170mA(MAX) | |
| Operating Temp. / Hum. | -10°C ~ +50°C / 30% ~ 80% RH | |
| Storage Temp. / Hum. | -20°C ~ +60°C / 20% ~ 90% RH | |

Dimension

Unit : mm

