

Secure life with **KCE**
GIMBAL DOME CAMERA



KCE-8845-E / KCE-8845W-E

Gimbal Dome Camera with Built-in Vari-focal Lens



- 1/3" 960H Sony EXview HAD II CCD
- 0.1Lux at F1.2
- Super High Resolution 700TV Lines
- 2.8~12mm Varifocal Lens
- Vandal Proof Housing
- Cable Management Bracket KCEDB-104 (optional)
- Dual Voltage DC12V/ AC24V
- 3-Axis Mounting Capabilities
- IP66 rated for weather proof



Specification

| DESCRIPTION | NTSC | PAL |
|------------------------|--|----------------------------|
| Image Sensor | 1/3" 960H Sony EXview HAD II CCD | |
| Effective Pixels | 976(H) x 494(V) | 976(H) x 582(V) |
| Scanning System | 2:1 Interface | |
| Synchronization | Internal | |
| Horizontal Resolution | 700TV Lines | |
| Video Output | CVBS : 1.0Vp-p, 75Ω composite | |
| S/N (Y Signal) | 52dB (AGC off) | |
| Min. Illumination | 0.1 Lux at F1.2 | |
| 3Axis | Yes | |
| Lens | 2.8~12mm Varifocal Lens | |
| Electronic Shutter | AUTO (1/60~1/10,000sec) | AUTO (1/50~1/10,000sec) |
| Backlight Compensation | AUTO | |
| White Balance | ATW | |
| AGC | AUTO | |
| Day&Night | AUTO | |
| IR LED | 45 EA | |
| Input Voltage | DC 12V(±10%) / AC 24V Dual Voltage | |
| Power Consumption | IR OFF : 250mA(max) / IR ON : 550mA at DC 12V POWER IR OFF : 170mA(max) / IR ON : 450mA at AC 24V POWER | |
| Operating Temp. / Hum. | -10°C ~ +50°C / 30% ~ 80% RH | |
| Storage Temp. / Hum. | -20°C ~ +60°C / 20% ~ 90% RH | |

Dimension

Unit : mm

