

KCE-8855-E

Gimbal Dome Camera with Built-in Fixed Lens



- 1/3" 960H Sony EXview HAD II CCD
- 0.1Lux at F1.2
- Super High Resolution 700TV Lines
- 6mm Fixed Lens
- Vandal Proof Housing
- Cable Management Bracket KCEDB-104 (optional)
- 3-Axis Mounting Capabilities
- IP66 rated for weather proof

Specification

DESCRIPTION	NTSC	PAL
Image Sensor	1/3" 960H Sony EXview HAD II CCD	
Effective Pixels	976(H) x 494(V)	976(H) x 582(V)
Scanning System	2-1 Interface	
Synchronization	Internal	
Horizontal Resolution	700TV Lines	
Video Output	CVBS : 1.0Vp-p, 75Ω composite	
S/N (Y Signal)	52dB (AGC off)	
Min. Illumination	0.1 Lux at F1.2	
3Axis	Yes	
Lens	6mm Fixed Lens	
Electronic Shutter	AUTO (1/60~1/10,000sec)	AUTO (1/50~1/10,000sec)
Backlight Compensation	AUTO	
White Balance	ATW	
AGC	AUTO	
Day&Night	AUTO	
IR LED	55 EA	
Input Voltage	DC 12V(±10%) Only	
Power Consumption	IR OFF : 170mA(max) / IR ON : 650mA at DC 12V POWER	
Operating Temp. / Hum.	-10°C ~ +50°C / 30% ~ 80% RH	
Storage Temp. / Hum.	-20°C ~ +60°C / 20% ~ 90% RH	

Dimension

Unit : mm

