

Secure life with **KCE**

VANDAL DOME CAMERA



KCE-1530-E

Vandal Dome Camera with Built-in DC Vari-focal Lens



- 1/3" 960H Sony EXview HAD II CCD
- 0.1Lux at F1.2
- Super High Resolution 700TV Lines
- 2.8~12mm DC Auto Iris Varifocal Lens(ICR Filter)
- Built-in OSD Controller & 2nd BNC output
- Vandal Proof Housing
- 3-Axis Mounting Capabilities
- DNR(Digital Noise Reduction)
- IP 66 rated for weather proof

Specification

DESCRIPTION	NTSC	PAL
Image Sensor	1/3" 960H Sony EXview HAD II CCD	
Effective Pixels	976(H) x 494(V)	976(H) x 582(V)
Scanning System	2:1 Interface	
Synchronization	Internal	
Horizontal Resolution	700TV Lines	
Video Output	CVBS : 1.0Vp-p, 75Ω composite	
S/N (Y Signal)	52dB (AGC off)	
Min. Illumination	0.1 Lux at F1.2	
OSD	ON / OFF	
IRIS Adjustment	MANUAL / AUTO(DC)	
Lens	2.8~12mm DC Auto Iris Varifocal Lens (ICR Filter)	
Electronic Shutter	AUTO / MANUAL (1/30~1/10000sec)	AUTO / MANUAL (1/30~1/10000sec)
Backlight Compensation	ON / OFF / OFF	
White Balance	STD / WASH / GREEN / USER2 / WTI / ON / MANUAL / PUSH LOCK	
AGC	MANUAL / AUTO	
ATR	ON / OFF	
Mirror	ON / OFF	
Day&Night	COLOR / AUTO / BW	
Privacy	ON / OFF / 4 zones	
DNR	YES Level Adjustment	
Language	English / Japanese / German / French / Russian / Portuguese / Spanish	
Motion	ON/OFF	
IR LED	30 EA	
Input Voltage	DC 12V(±10%) / AC 24V Dual Voltage	
Power Consumption	IR OFF: 250mA(max) / IR ON: 550mA at DC 12V POWER IR OFF: 170mA(max) / IR ON: 430mA at AC 24V POWER	
Operating Temp. / Hum.	-10°C ~ +50°C / 30% ~ 90% RH	
Storage Temp. / Hum.	-30°C ~ +60°C / 20% ~ 90% RH	

Dimension

Unit : mm

